

**INDEX OF CTL / ECS OSM-LUM DECISION SHEETS**  
**October 2011**

**CTL – ETF5 (LITE – SAFE)**  
**LUMEX INTERPRETATION PANEL**  
**OPERATIONAL STAFF MEETING LUMINAIRES**

<i>No.</i>	<i>SUB-CLAUSE</i>	<i>SUBJECT</i>
<b><u>IEC/EN 60598-1</u></b>		
<i>0807</i>	<i>General</i>	<i>Luminaires system for 230V</i>
<i>0808</i>	<i>General</i>	<i>IEC 62262 / EN 50102</i>
<i>0809 + Fig.</i>	<i>General / 1.7</i>	<i>Fixed luminaire with track</i>
<i>0810</i>	<i>General</i>	<i>Metallic paint</i>
<i>0811</i>	<i>General</i>	<i>Luminaires for the use with independent control gear</i>
<i>0812</i>	<i>General</i>	<i>LEDs used as a light source in luminaires</i>
<i>0813</i>	<i>General</i>	<i>E27 to G9 and GU10 lampholders adapters</i>
<i>0814</i>	<i>General / 1.2.60 2.2</i>	<i>T8 to T5, T8 to T8 and similar lamp adaptors (including ditto with LED)</i>
<i>0816</i>	<i>0.2</i>	<i>Socket-outlet mounted rechargeable luminaire Rechargeable lamps luminaires</i>
<i>0817 + Fig.</i>	<i>0.4</i>	<i>Floodlight with mounting accessories</i>
<i>0818</i>	<i>0.4.2</i>	<i>Instruction manual of a floodlight</i>
<i>0819</i>	<i>0.4.2 / General</i>	<i>Luminaires needing assembly by the user</i>
<i>0820</i>	<i>0.4.2 / 12</i>	<i>Luminaires needing reconnection by the installer</i>
<i>0821</i>	<i>0.5</i>	<i>Use of 230V components in 240V luminaires</i>
<i>0822</i>	<i>0.5</i>	<i>Series – compensated luminaire (working voltage)</i>

0823	0.5	Connecting device with fuse holder
0824	0.5	Luminaire marked for lamp GU 5,3
<b>0402/10 ECS</b> <b>OSM/LUM</b>	<b>0.5</b>	<b>Components</b>
<b>0403/10 ECS</b> <b>OSM/LUM</b>	<b>0.5</b>	<b>Luminaires provided with socket-outlets</b>
<b>0404/10 ECS</b> <b>OSM/LUM</b>	<b>1.2.60</b>	<b>T5 adapter</b>
0825	1.2.81 / 4.14.3	Temperature of “means of adjustment”
0826	Sections 2- 3	Classification and marking of Class II with Class III detachable parts
<b>0405/10 ECS</b> <b>OSM/LUM</b>	<b>2.4 / 3.2.7 /</b> <b>3.2.9</b> <b>3.3.4 / 2.5.1</b>	<b>F-marking on recessed luminaires</b>
0827	3	Definition of basic type reference
0828	3	Marking of lamp types according to IEC Technical Specification 61231
0829 + Fig.	3	Marking on class III luminaires “system”
0830	3.2	Marking on small luminaires
0831	3.2.2	Rated voltage marking
0832	3.2.6	Marking with IP numbers
0833	3.2.6	“IP X8” marking
0834	3.2.6 / 9.2	IP test on recessed luminaires
0835	3.2.8	Lamp-type information marking
0836	3.2.13	Symbol for minimum distance from lighted object
0837	3.2.16	Protective shields
0838	3.3	Markings / additional information
0839	3.3.10	Marking – Additional information
0840	3.3.7 / 4.24 Annex P	UV radiation

0841	4.2 / 8.2.1	Luminaire with fuse holder / fuse
0842	4.2 / 15.7	Non-detachable flexible cable or cord
0843	4.4.4	Lampholder fixed by the shade ring
0844	4.4.4 ii)	Lampholder mounting brackets
0845 + Fig.	4.7.2	Supply terminals (8 mm free wire)
0846	4.7.3	Lampholder terminals
0847	4.7.4	Terminals for internal and external connections
0848	4.8	Switches for luminaires
0849	4.10	Insulation required for external and SELV wiring
0850	4.10.1	Double and reinforced insulation
0851	4.11.1	Contact pressure
0852	4.11 / 4.12	Luminaires to be assembled by the user
0853	4.11.3	Locking device for screws
0854 + Fig.	4.11.3	Screw connections
0855 + Fig.	4.11.3	Electrical connections
0856 + Fig.	4.11.3 / 7	Crimped connections
0857	4.11.3 / 7.2.4	Rivets for electrical and mechanical connections
0858	4.11.4	Material with equivalent characteristics
0859	4.11.5	Wooden parts on luminaires
0860	4.12.4	Portable luminaire; different parts can be loosen by hand
0861 + Fig.	4.14	Suspension devices
0862	4.14	Suspension devices for recessed luminaire
0863	4.14.1	Clip-mounted luminaire
0864 + Fig.	4.14.1	Clip-mounted luminaire: pulling test
0865	4.14.3	Screw adjustable by the user
0866	4.15	Flammable materials
0867	4.15	Heated part
0868	4.15 / 12.7.1	Application of clauses 4.15 and 12.7.1
0869	4.15 / 12.7.1	Application of the linear regression formula
0870 + Fig.	4.15a) / 12.7.1	Luminaires in thermoplastic material (fixing points)

0871	4.16	Temperature sensing control device
0872	4.16.2 / 12.6.2	Temperature sensing controls
0873	4.24	Annex P
0874	4.24	Annex P
0875	4.24	Use of different M.H. lamps
0876	4.24	Protective shield
0877	5.2	Non standardised plug for class III luminaire
0878	5.2.2	Insulation required on a cable (SELV operating)
0879	5.2.2	External wiring for low voltage luminaire
0880	5.2.2 / 5.3.5	Internal wiring for ordinary luminaires
0881	5.2.2 / 7.2.11	Transparent flexible cords
0882	5.2.10	Cord anchorage
0883	5.2.10 / 5.3.5	Cord anchorage on lampholder
0884	5.2.10 / 5.3.5	Cord anchorage on adjustable luminaire
0885	5.2.10 / 5.3.5	Recessed luminaire delivered with separate control gear
0886	5.2.10.2 / 5.2.10.3	Cord anchorage with type Y or Z attachment on Printed Circuit Board
<b>0408/10 ECS OSM/LUM</b>	<b>5.2.14 / Annex ZB</b>	<b>Portable luminaire</b>
0887	5.3	PTFE basic insulated cable
0888	5.3	Internal wiring for some lamp circuits
0889	5.3.1	Through wiring in the luminaires
0890	5.3.3	Use of additional sleeves
0891 + Fig.	7.2	Locking on earthing connection
0892	7.2.1	Earthing in luminaire system
0893	7.2.1	Electrical connections
0894 + Fig.	7.2.4	Reliability of the earthing circuit
0895	8	Standard test finger
0896	8.2.1	Luminaires with LEDs
0897	8.2.1	Live metal parts projected from Edison screw caps

0898 + Fig.	8.2.1 / 8.2	G10q – connector's construction	
0899	8.2.3	Class II luminaire with metal reflector	
0900	8.2.3	Metal fixing devices for components	
0901	8.2.3	Luminaire with PGZ12 lamp cap	
0902 + Fig.	8.2.5	Class II luminaires for discharge lamps	
0903	9.	IP 65 luminaire	
0904	9.	IP 20 luminaire	
0905	9. / 9.2	IP X3 / IP X4 tests	
0906	9.2	Torque for fixing screws of covers	
0907	9.2	Test for ingress of moisture	
0908 + Fig.	9.2 f	Entry of test probes for IP 3X and 4X	
0909 + Fig.	9.2.0	IP 40	
0910 + Fig.	10	Dielectric strength test on bushing	
0911	11	Distances inside a lamp	
0912	11	Supply terminals – creepage distances and clearances	
0913	11	Touch lamp	
0914 + Fig.	11.2	Creepage and clearances between a metal reflector and the cap of a fluorescent lamp	
0915	11.2.1	Pendant luminaire with a "ceiling cone"	
0916	11.2.1	Creepage distances and clearances at a supply terminal	
0917	12	Heating tests for tungsten halogen lamps	
0918	12	Endurance and thermal tests	
0919	12	Luminaires provided with LEDs	
0920 + Fig.	12.1	Temperature limits of the external parts (metal) of a fixed luminaire	
0921	12 – Table 12.2	Temperature limits for rubber cables	
0922	12.4	Clarification of some luminaire parts	
0923	12.4.1	Temperature limit on terminal block	

0924	12.4.2	<i>Sleeve for earthing supply cable</i>	
0925	12.5.1	<i>Abnormal operation condition</i>	
0926	12.5.1.4)	<i>Luminaire inoperative after the test</i>	
0927	12.7.1	<i>Fault condition test</i>	
0928	13.2.1	<i>Ball pressure test on soft thermoplastic</i>	
0929	13.2.1	<i>Temperature for ball pressure test</i>	
0930	13.3.1	<i>Needle flame test / glow wire test</i>	
0931	<i>Annex C</i>	<i>Self-ballasted lamps luminaires</i>	
0932 + Table 1	<i>Annex C</i>	<i>Luminaires for M.H. lamps</i>	